

MATERIAL SAFETY DATA SHEET from STEARNS PACKAGING CORPORATION

SECTION I—PRODUCT/MANUFACTURER'S IDENTITY

IDENTITY (As Used On Label and List):

Heavy Duty Degreaser

SYNONYMS: ST-905, ST-1261

FORMULA ID NUMBER: CM-40

EPA REG #: None

NSF CERTIFIED: A1, 7/20/04

COMPANY: STEARNS PACKAGING CORPORATION
ADDRESS: 4200 Sycamore Ave. (53714), P.O. Box 3216
Madison, Wisconsin (WI) 53704-0216

PHONE: 1 (608) 246-5150
FAX: 1 (608) 246-5149
INTERNET: www.stearnspkg.com
EMAIL: stearns@stearnspkg.com

HAZARD RATING		
0	Flammability	4 = Extreme
3	Health	3 = High
0	Reactivity	2 = Moderate
None	Special Hazard	1 = Slight
		0 = Insignificant

For Transportation Emergency Involving Hazardous Materials Contact: CHEM-TEL 1 (800) 255-3924

Shipping Information:

DOT SHIPPING NAME: Compounds, cleaning liquid, (containing sodium metasilicate), 8, NA 1760, PG III, Item 48580, Sub. 3, Class 55

DOT SHIPPING NAME: ST-905
Compounds, cleaning liquid, (containing sodium metasilicate), 8, NA 1760, PG III, Ltd Qty. Item 48580, Sub. 3, Class 55

DOT SHIPPING NUMBER: ST-1261
NA 1760
HAZARD LABEL: Corrosive; None for Ltd Qty
HAZARD CLASS: 8, Corrosive

SECTION II—HAZARDOUS INGREDIENTS OR IDENTITY INFORMATION

HAZARDOUS CHEMICAL IDENTITY &

<u>CAS#</u>	<u>HAZARD</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OTHER LIMITS</u>	<u>% (OPTIONAL)</u>
▶ Sodium metasilicate pentahydrate 6834-92-0	Corrosive				
▶ Nonylphenol ethoxylate 127087-87-0	Irritant				
▶ Tripotassium phosphate 7778-53-2	Irritant				

SARA SECTION 313 TITLE III NOTIFICATION REQUIRED: No

SECTION III—PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT:	Not Determined	VAPOR PRESSURE (mm Hg):	Not Determined
SPECIFIC GRAVITY (WATER=1):	1.12	VAPOR DENSITY (AIR=1):	Not Determined
MELTING POINT:	Not Applicable	EVAPORATION RATE:	Not Determined
SOLUBILITY IN WATER:	Complete	pH (CONCENTRATE):	13.47
APPEARANCE AND ODOR:	Clear green liquid	pH (1% SOLUTION):	Not Determined

SECTION IV—FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED):	Non-combustible, >200°F
EXTINGUISHING MEDIA:	CO ₂ , water, dry chemical
FLAMMABLE LIMITS:	LEL: Not Applicable UEL: Not Applicable
SPECIAL FIRE FIGHTING PROCEDURES:	Use full protective clothing and self-contained breathing apparatus.
FIRE & EXPLOSION HAZARDS:	None

SECTION V—REACTIVITY DATA

STABILITY:	Stable
INCOMPATIBILITY (MATERIALS TO AVOID):	Strong acids
HAZARDOUS DECOMPOSITION OR BYPRODUCTS:	None known
CONDITIONS TO AVOID:	Do not mix with strong acids. Avoid freezing and extremes of heat.
HAZARDOUS POLYMERIZATION:	Will not occur

SECTION VI—HEALTH HAZARD DATA/FIRST AID PROCEDURES

HEALTH HAZARDS (ACUTE AND CHRONIC): Irritation of exposed tissues. Chronic exposure causes burns. Eyes, skin, and mucous membranes may be simultaneously irritated or burned if exposed to mists of product or solutions.

CARCINOGENICITY: NTP: No
IARC Monographs: No
OSHA Regulated: No

SIGNS AND SYMPTOMS OF OVEREXPOSURE: **Skin:** Irritation or corrosion may occur to exposed tissues, especially eyes, skin, throat, nasal cavities and other mucous membranes from contact with the product, its use solutions, or mists and vapors generated by the product. Brief contact with skin may cause irritation or rash. Prolonged contact may cause skin burns and ulceration. **Eyes:** Eye contact may cause blindness. Liquid may irritate or corrode eyes, causing discomfort, tearing or blurring of vision. Prolonged contact may lead to eye corrosion with corneal or conjunctival ulceration. **Ingestion:** Ingestion may be harmful or fatal. Ingestion will cause burning of tissues, abdominal pain, nausea, vomiting and collapse. Swallowing large quantities may cause death.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: No data available.

EMERGENCY AND FIRST AID PROCEDURES:

Eyes: If contact with eyes occurs, flush with plenty of cool water for 15 minutes. Consult a physician.
Skin: May be irritating to skin. If contact occurs, flush with water and wear gloves in the future to minimize exposure. Wash hands thoroughly after handling. Discontinue use if irritation persists and consult a physician.
Inhalation: Remove from exposure. Obtain medical attention immediately.
Ingestion: May be harmful if swallowed. If ingested, drink large amounts of water or milk. **DO NOT** induce vomiting. Get medical attention immediately. Avoid contamination of foods.
Note to Physician: No specific antidote. Use supportive care. Treatment should be based on judgment of the physician in response to the reactions of the patient.

SECTION VII—PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Protective clothing and equipment must be worn by personnel. Contain spills or leakage in suitable containers or contain in a holding area. Do not allow drainage to sewers, streams, or storm conduits. Recover with vacuum equipment such as a septic tank truck or neutralize with weak acid solutions (such as acetic acid) and flush with water to a sanitary sewer. Avoid splashing and misting which could increase health hazards.

WASTE DISPOSAL METHOD: Waste disposal must be done in accordance with all local, city or municipality, county, state, and federal regulations. Consult your state department of natural resources or the EPA for specific questions not answerable through other sources. Wastewater should never enter a fresh water body without treatment. If material cannot be salvaged, an acceptable method of disposal is neutralization followed by discharge into treatment system with large amounts of water.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Wear all recommended safety gear. Do not mix with other chemicals or cleaning agents. Do not store near acids or metals like aluminum, tin, or zinc.

OTHER PRECAUTIONS: Always keep product out of the reach of children.

SECTION VIII—OTHER REGULATORY INFORMATION

California Safe Drinking Water and Toxic Enforcement Act of 1986: Ethylene oxide 75-21-8

SECTION IX—CONTROL MEASURES

RESPIRATORY PROTECTION: In general, respirators are not needed if the product is used in a well-ventilated area. However, use of a NIOSH/MSHA respirator may be a good common sense approach to working with products where dusts and mists are known to cause irritation of the eyes and/or mucous membranes.

VENTILATION: Local Exhaust: Recommended to control below TLV of 2 ppm for sodium hydroxide.
Mechanical (General): Recommended to control below TLV of 2 ppm for sodium hydroxide.

SKIN PROTECTION: Neoprene, rubber, or other chemical resistant gloves. Wear protective clothing to prevent repeated or prolonged contact.

EYE PROTECTION: Splash goggles, or safety glasses if splashing is not a concern.

WORK/HYGIENIC PRACTICES: As good hygiene dictates.

Stearns Packaging Corporation makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Stearns Packaging Corporation as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Stearns Packaging Corporation assume any liability arising out of the use by others of this product referred to herein. The data in this MSDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Stearns Packaging Corporation does not recommend blending this product with any other chemicals. All information, recommendations and data contained herein concerning this product are based upon information available at the time of writing from recognized technical sources.